

C A T A L O G

ENERGY RANGE



Contract PMUC : n°C9498T0900



ORAPI

CLEAN & PROTECT TOGETHER



THE ONLY FRENCH MANUFACTURER VERTICALLY
INTEGRATED FROM DESIGN TO MARKETING

PENETRATE & RELEASE

REDUCE 2N

815

HALOGEN-FREE

Lubricating, de-seizing fluid with high penetrative power. Dissolves the residue formed by mounting pastes. Lubricates and protects. Penetrates, removes rust, dissolves tar and dirt on the dirtiest parts, infiltrates even the narrowest spaces. Very effective against salt water corrosion.

PMUC 04-033

Cl - F - S - Br :
< 200 ppm


6815A2	405 ml aerosol TDS	x12
6815i1	500 ml spray bottle	x12
6815J1	5l jerrycan	x4



CLEAN



GIVREUR 2

9512

COLD GENERATOR

Generates intense cold. Multi-positions. De-seizes by thermal shock. Used in the IT industry to cool microprocessors and overheated hardware. Enables the detection of printed circuit board failures. Can also be used with mechanical devices to retract parts and allow shrink-fitting.

T° : -52°C



49512A4	650/500 ml aerosol	x12
---------	--------------------	-----

GREASES

SI 20

646

SILICONE GREASE

Enhanced anti-wear and anti-corrosion properties. For bearings, hinges and mechanisms operating in very humid atmospheres at high speeds and under medium loads. Absorbs heat energy.

■ beige
T° : -30 à +160°C


3646B7	Box 1 kg	x6
3646O4	50 kg drum	x1

CT 300

628

INFUSIBLE GREASE

Grease with outstanding extreme pressure lubricating properties at high temperatures. Not soluble in water. No drop point, does not run, even if subjected to overheating. Recommended for steelworks: rolling mills, rubber, cardboard, paper industries etc. for main bearings, roller bearings etc.

■ light brown
T° : -40 à +210°C


3628C4	400 g cartridge	x12
3628S1	5 kg tub	x2
3628O4	50 kg drum	x1

SI 450

648

GRAISSAGE DES JOINTS

Silicone grease for assembling joints and lubricating all mechanisms in contact with water. Water repellent. Excellent thermal conductivity, chemically inert. Keeps rubber gaskets flexible. Protection of all electrical devices. Suitable for greasing all elastomers.

■ colourless
T° : -40 à +200°C
Water resistance:
very good
Cl - F - S - Br :
< 200 ppm


PMUC 19-172

6648T4	200 g tube	x12
6648B7	1 kg tin	x6

CT 51 NF

629

HALOGEN-FREE

Versatile, multi-purpose grease for all types of mechanism: bearings, hinges, runners etc. Water and solvent resistant.

■ White
T° : -20 à +160°C
Cl - F - S - Br :
< 200 ppm


PMUC 19-0533

6629T3	100 g tube	x12
2515J1	400 g cartridge	x12
2515O1	1 kg tin	x6
2515U2	25 kg drum	x1

GREASES

VASCO 15

658

HALOGEN-FREE VASELINE

Chlorine-free, sulphur-free, fluorine-free Vaseline codex grease, specifically designed to lubricate small, delicate mechanisms and joints. Delicate greasing of plastics, ways, cables, grooves, runners, locks.

PMUC 19-084

■ White
T°: -20 à +50°C
Grade NLGI : 4 / 5
résistance water :
Good
Cl - F - S - Br :
< 200 ppm



6658T3	100 g tub	x12
6658B7	1 kg tin	x6

CT 14

602

MULTI-PURPOSE, LITHIUM-BASED

Multi-purpose EP2 grease for bearings and mechanisms subject to heavy loads. Ideal for industrial applications, automobiles, trucks etc.

■ light amber
T°: -30 à 165°C
Grade NLGI : 2
EP 4 billes :
315 kg
DN Factor :
350 000

4602A4	650 ml aerosol	x12
3602T3	100 g tube	x6
3602C4	400 g cartridge	x12
3602B7	1 kg tin	x6
3602S1	5 kg tub	x2
3602O2	25 kg drum	x1
3602O4	50 kg drum	x1
3602U1	180 kg drum	x1



CT 4

608

MOS2 GREASE

Greasing under very heavy loads, effectively combats wear thanks to its concentration of high quality MoS2. Mechanical construction, automotive industry, arms industry etc. Safe lubrication of bearings..

■ grey/black
T°: -30 to +165°C
NLGI Grade: 2
4-ball EP:
315 kg
DN Factor:
350 000



4608A4	650 ml aerosol	x12
3608T4	200 g tube	x12
3608C4	400 g cartridge	x12
3608B7	1 kg tin	x6
3608S1	5 kg tub	x2
3608O2	25 kg drum	x1
3608O4	50 kg drum	x1

CT 12 G

625

GRAPHITE GREASE

Greasing under very heavy load, fights effectively against wear thanks to the presence of micronised graphite. Has an extremely low coefficient of friction. Humid conditions and mechanisms subject to shocks. Ideal for applications in the automotive industry, trucks and general industry.

■ black
T°: -30 to +130°C
NLGI Grade: 2
4-ball EP:
315 kg
DN Factor:
350 000

3625C4	400 g cartridge	x12
3625B7	1 kg tin	x6
3625O2	25 kg drum	x1



CT 143

743

LUBRICATION/SEALING

Valves and taps can be sealed and lubricated in a single operation thanks to the thick, paste like consistency of this product. Multipurpose EP3 grease for bearings and other mechanisms that require a thick grease. Ideal for industrial applications, cars and trucks.

■ amber
T°: -30 to +165°C
Drop point:
180
NLGI Grade: 3
4-ball EP:
315 kg
DN Factor:
350 000



3743B7	1 kg tin	x6
--------	----------	----

WSA

605

MARINE GREASE

Adheres, resists water and steam. Multipurpose. Suitable for the marine environment and hydraulic industries. Bearings, axles, runners etc. Port areas, water treatment plants.

■ green
T°: -30 to +130°C
4-ball EP:
315 kg
DN Factor:
500 000

4605A4	650 ml aerosol	x12
3605T4	200 g tube	x12
3605C4	400 g cartridge	x12
3605B7	1 kg tin	x6
3605S1	5 kg tub	x2
3605O2	25 kg drum	x1
3605O4	50 kg drum	x1
3605U1	180 kg drum	x1



CTDMEP 2

606

HIGH-TEMPERATURE GREASE

Top range grease for heavy loads and high temperatures. Paper mills, public works, textiles, cardboard plants, steelworks. Excellent resistance in humid environment. Excellent stability for long lasting use.

■ blue
T°: -30 to +180°C
4-ball EP:
315 kg
DN Factor:
500 000



3606C4	400 g cartridge	x12
3606B7	1 kg tin	x6
3606S1	5 kg tub	x2
3606O2	25 kg drum	x1
3606O4	50 kg drum	x1
3606U1	180 kg drum	x1

CT 8 EP

617

EXTREME PRESSURE MOS2 GREASE

MoS2 lubricant specifically formulated for use in very hot and exacting environments. Public works, transport, car equipments, mines, boiler rooms. Greatly reduces noise and mechanism wear.

■ grey / black
T°: -20 to +230°C
4-ball EP:
315 kg

3617B7	1 kg tin	x6
--------	----------	----



GREASES

SIL 50/50

823

SURFACE TREATMENT

MoS₂ silicone paste. Exceptional resistance to corrosive chemicals, water, steam and oxidation. Lubrication of mechanisms exposed to very low and very high temperatures. Widely used in aeronautics.

■ Bluish grey
T°: -50 to +300°C
NLGI Grade: 1
4-ball EP:
500 kg

3823T3 100 g tube x12

CT 609

609

TRANSLUCENT GREASE

Highly fluid, clean lubricant for greasing delicate mechanisms. For lubricating micro-mechanisms, control apparatus, pneumatic circuits and chains in the food industry. Recommended by SEDIS. INS 3H for direct contact with foodstuffs.

4609A4	650 ml aerosol	x12
3609T4	200 g tube	x12
3609C4	400 g cartridge	x12
3609B7	1 kg tin	x12
3609S1	5 kg tub	x12
3609O2	25 kg drum	x12
3609O4	50 kg drum	x4



transparent
T°: -30 to +150°C
Drop point :
none



OILS

G 840

840

GLYCERIN OIL

Refined lubricant for delicate greasing. Very fluid, to be used for lubrication of micro-mechanisms, control devices and pressure gauge filling. Does not stain.

PMUC 19-108



colourless
T°: -20 to +70°C
Viscosity at 25°C:
800 cP
Cl - F - S - Br :
< 200 ppm



6840i2 1 l container x12
684001 20 kg drum x1

ORAFLOX

705

PTFE LUBRICANT

High-technology, semi-greasy PTFE lubricant for long-lasting use. Reinforced anti wear and anti oxidation properties, excellent adherence. Very low friction coefficient. Excellent resistance to water and cold. For chains, cables, slides, delicate mechanisms...

■ light amber
T°: -20 to +230°C

4705A2	405 ml aerosol TDS	x12
2705i2	1 l container	x12
2705J1	Jerrycan 5 l	x4



ORACOUF 892

892

HALOGEN-FREE

Micro-emulsion for milling, turning and sawing of ferrous metals and white alloys, appropriate for high volume metal chip removal. Product with excellent mechanical and microbial stability, allows for less frequent emptying.

PMUC 19-070

■ Yellow
Usage dose:
2 to 6%
pH to 5%:
9 to 10
Cl - F - S - Br :
< 200 ppm

6892J1	5 l can	x4
6892O5	60 l drum	x1
6892U2	200 l drum	x1



FTS 10 NU

865

ODOURLESS AND COLOURLESS

Synthetic colourless and odourless fluid with high anti wear and extreme pressure power. For the tapping and drilling of all metals, prevents the premature wear of cutting tools. To be applied neat, with brush or by spraying.

PMUC 19-071

colourless
odourless
Viscosity at 20°C:
180 cSt
Cl - F - S - Br :
< 200 ppm



6865i1 500 ml spray bottle x12

2000 NUCL NF

858

HALOGEN-FREE

Cutting oil with excellent extreme pressure and anti-wear properties, free from halogen compounds; quickly dissipates the heat energy generated by machining. Its formulation and viscosity make it suitable for all uses on all materials, more specifically titanium and stainless steel machining in the nuclear and aeronautical industries.

PMUC 19-0527

■ yellow
Viscosity at 40°C:
21 cSt
Cl - F - S - Br :
< 200 ppm

6858A4	650 ml TDS aerosol	x12
6858i1	500 ml can	x12
6858J1	5 l jerrycan	x4
6858U2	200 l drum	x1



OILS

SILICONE SPRAY 803

LUBRICANT AND MOULD RELEASER

Aerosol version of silicone oil for easy and precise release. Excellent for releasing from rubber and plastic moulds. Very strong water repellent power. Withstands frequent cleaning. Lubrication of guillotine table and blade. Non-adhesive, antistatic lubrication of conveyor belts and slideways in the packaging and textiles industries.

colourless
T°: -50 to +200°C

PMUC 19-208

6803A4 650 ml aerosol x12



FINE 121

810

MULTI-USAGES AU LITHIUM

Highly fluid, clean lubricant for greasing delicate mechanisms. For lubricating micro-mechanisms, control apparatus, pneumatic circuits and chains in the food industry. Recommended by SEDIS. INS 3H for direct contact with foodstuffs.

PMUC 19-0532

6810R1 125 ml oil can x12
6810A4 650 ml aerosol TDSI x12
6810I2 1 l container x12



colourless
T°: -30 to +150°C



PROCESS - ASSEMBLE

GRN

613

HALOGEN-FREE GRAPHITE

Chlorine-free, sulphur-free and fluorine-free anti seize paste, stable at high temperatures. Mechanical assemblies. Facilitates the running-in and dismantling of parts.

■ black
T°: -80 to +900°C
4-ball EP:
250 kg
Cl - F - S - Br :
< 200 ppm

PMUC 04-016

6613A4 650 ml aerosol x12
6613T4 200 g tube x12
6613B6 500 g tin x6



TM900S

600

COPPER

Copper-based assembly paste for surface treatment and lubrication. Specifically designed to treat: tools, axles, rollers, slow-moving parts and all parts that will need dismantling. Recommended for pouring nozzles in steelworks. Electrical and thermal conductor.

■ copper
T°: -40 to +1 100°C

3600A4 650 ml aerosol x12
3600B4 250 ml tin with brush x 6
3600T4 200 g tube x12
3600C4 400 g cartridge x12
3600B7 1 kg tin x6
3600O2 25 kg drum x1
3600O4 50 kg drum x1
3600U1 180 kg drum x1



HT 600

601

ALUMINIUM

Contains a special base and micronised aluminium. Particularly effective for treating: tools, axles, rollers, slow movements and any part that must be dismantled.

■ aluminium
grey
T°: -40 to +650°C

4601A4 650 ml aerosol x12



NB

643

WHITE, HALOGEN-FREE

Anti-seize boron nitride paste for assemblies exposed to very high temperatures. Mounting of all assembled parts that will need to be dismantled easily. Chlorine-free, fluorine-free, sulphur-free.

■ White
T°: -80 to +1 400°C
Cl - F - S - Br :
< 200 ppl

PMUC 04-0107

6643B4 Tin with brush 250 ml x6
6643B6 500 g tin x6



GRAPHENE PMUC 702

GRAPHITE

For the pre-treatment of surfaces or parts subject to very high temperatures or dusty atmospheres. Dries at room temperature. Excellent resistance of dry film. For stainless steel assembly with itself, tin mould releasing. Lubrication of runners, rods, glass etc.

■ black
T°: -70 to +900°C
Grading :
5 µm

PMUC 04-0104

6702A4 650 ml aerosol x12



A20N NF

717

HALOGEN-FREE GRAPHITE VARNISH

Colloidal dispersion of micronised graphite in a binder. Forms a dry, smooth and adherent lubricating film. Resists to abrasion and gives metallic moving parts an excellent lubrication. Facilitates assembling and enables non-destructive dismantling. In particular stainless steel/stainless steel assemblies. Ideal in dusty atmospheres and for applications in very cold environments.

■ black
T°: -70 to +900°C
Cl - F - S - Br :
< 200 ppm

PMUC 04-037

6717I2 1 l container x12



PROCESS - ASSEMBLE

MOB 60

611

MOS2 HIGH-CONCENTRATION GRAPHITE

Strong formula. Mechanics use this paste for the most difficult fixings. For breaking in and pretreatment, use this paste with a leather cloth or with a brush. Strong resistance to extreme pressure. For all hard assembly. Prevents fretting corrosion. Mechanical workshops, fixing, maintenance.

■ black
T°: -60 à +450°C



3611T4	200 g tube	x12
3611B7	1 kg tin	x12



SURFACE PREPARATION

ACTIVATEUR 6140

025

SPECIFICALLY FOR GLUES

Decreases setting time significantly for glues and enables polymerisation outside of gluing area. Apply ACTIVATEUR 6140 on one of the surfaces and the glue on the other surface or directly on the glue to activate polymerisation

colourless
liquid
Evaporates quickly

1025i2	1 l container	x12
--------	---------------	-----

ACTIVATEUR 3140

015

WHOLE CUTTING OIL

Speed up the polymerisation of anaerobic resins, reducing setting time.

Recommended:

- for use on galvanised or painted surfaces, stainless steel and aluminium,
- for large gaps
- when the temperature is below 10°C

PMUC 16-055

6015M1	100 ml pump spray	x12
--------	-------------------	-----

NSF

■ copper red
liquid



ADHESIVES

ORABOND 129

129

QUICK-SETTING ADHESIVE PUTTY

Flexible, bi-component quick-setting putty glue formulated for bonding and sealing on all materials. This new generation hybrid polymer glue is odourless and has higher tensile, tearing and shear strength than silicones and polyurethanes..

■ Off white
T°: -40 to +90°C
Shore A hardness:
40-50



1129C6	250 ml cartridge	x12
700093	Cannula	x12

ORABOND 125

125

VERY HIGH PERFORMANCE PRODUCT

Bonds, assembles and seals everything. New generation elastic putty sealant. Excellent adhesion to stainless steel, aluminium, wood, zinc, lacquer, stone, glass wool, chipboard, etc. Can be applied onto humid surfaces and surfaces completely immersed under water. Can be painted. Odourless. Does not drip. Ideal for replacing stainless steel/stainless steel welds. Very high tackiness

NSF

■ white
T°: -40 to +150°C
Shore A hardness:
45-60
Consumption:
1 cartridge = 1.5
m2 or 15 m



1125C6	290 ml cartridge	x12
--------	------------------	-----



NEOPRENE

400

MULTI-PURPOSE CONTACT ADHESIVE

Instant setting on rubber, leather, fabric, cork, metals, laminates. Flexible, high efficiency. Very high resistance to pull out, excellent resistance to moisture. Applied to both surfaces (150 ml/m2 per side).

■ beige
Setting time:
5 to 15 mn
Max T°: +90°C
Resistance to
peeling:
15 kg/cm²



4400A4	650 ml aerosol	x12
--------	----------------	-----

ADHESIVES

OREPOX 5

202

FAST-ACTING EPOXY, SETS IN 5 MIN

Epoxy resin with quick setting. Repair and rigid adhesion of most materials: ceramic, wood, cement, metal etc. Rapid gluing of poorly aligned or unaligned parts with large or variable gaps.

colourless
Mixture ratio: 1/1
T°: -40 to +100°C
Shelf life of mixture:
4 to 5 mn
Shearing strength:
15 MPa



1202E1	28 g syringe	x12
1202E3	50 ml syringe	x6
1202K7	1 kg kit	x1


THERMIQUE

418

HIGH-TEMPERATURE PUTTY GLUE

Silicone-free putty glue. Jointing, bonding and sealing, specifically formulated to withstand very high temperatures. Asbestos-free. Hardens completely, to the very centre. Do not use in contact with water. For cracks or holes filling-in, over metal, stones or concrete... Stoves, boilers, furnaces, open fireplaces, probes, car exhaust pipe fittings.

■ Anthracite grey
T°: -40 to +1200°C
Thickness:
5 to 15 mm
Shore A hardness:
70 to 90



16-0198

141C3	310 ml cartridge	x12
-------	------------------	-----

C2040

355

ELASTOMER

Quick-setting adhesive for bonding rubber joints, plastic, glass and O-rings.



colourless
T°: -50 to +80 °C
Viscosity:
20-40 cP
Setting time:
5 to 60 s
Shearing strength:
27,5 MPa



1355F1	5 ml bottle	x12
1355F2	20 ml bottle	x6
1355F3	50 ml bottle	x6

C 5000/14

385

MULTI-PURPOSE

Fluid glue with ultra rapid setting thanks to a special catalyst. Multi-purpose: glass, plastic, metals, wood etc. Chlorine-free, sulphur-free, fluorine-free, bromine-free.

colourless
T°: -50 to +80°C
Viscosity:
80-120 cP
Setting time:
5 to 40 s
Shearing strength:
27,5 MPa



16-053

6385F1	5 g bottle	x24
6385F2	20 g bottle	x6

C 5040

386

ELASTOMERS AND PLASTICS

Quick-setting chlorine-free, sulphur-free, fluorine free and bromine-free adhesive for bonding rubber joints, plastic, glass and O-rings. Good resistance to humidity. Bonding of silicone joints after surface preparation with 021.

colourless
T°: -50 to +80°C
Viscosity:
20 - 40 cP
Shearing strength:
> 25 MPa



16-052

6386F1	5 g bottle	x24
6386F2	20 g bottle	x6

DECOLLEUR 3720

408

CLEANING AND REMOVAL OF GLUES.

Cleaning solvent for glue applicators and work tables with glue on them. Separation of glued assemblies. Works by soaking. Liquid to be used in a well ventilated area.

transparent liquid
Cl - F - S - Br:
< 200 ppm



16-054



6408F2	20 ml bottle	x6
--------	--------------	----

C 5000 CM

384

MULTI-PURPOSE GEL

Quick-setting chlorine-free, sulphur-free, fluorine free, bromine-free gel for the vertical or inverted bonding of porous materials such as wood. Sticks on most materials: aluminium, ABS, PVC, metals, wood...

colourless
T°: -50 to +80°C
Viscosity:
1000 - 2000 cP
Setting time:
20 to 90 s
Shearing strength:
10 to 30 MPa



16-047

6384F1	5 g bottle	x24
6384F2	20 g bottle	x6



WATERPROOFING

TUBELOCK C

367

PIPES AND NOZZLES

Sealing of threaded metal tubes and fittings up to 3 inches, for a speedy restart and medium resistance when dismantling. Low pressure sealing within minutes. Resistant to most chemical products. Quick setting on steel and brass. For stainless steel fittings, ACTIVATEUR 3140 should be used.

■ yellow-orange
Handling time:
on steel 2 to 10mn
T°: -60 to +150°C
Breaking strength:
10 - 20 N.m



1367F7	50 ml squeeze bottle	x6
1367T2	50 ml tube	x6
1367T4	200 ml tube	x2

PORALOCK

328

THREAD SEALING, HIGH RESISTANCE

Liquid sealing compound for metal, hydraulic or pneumatic fittings and threaded fittings subjected to severe vibration. Unaffected by hydraulic and synthetic fluids, most industrial fluids and gases, hot and cold water etc. Replaces pastes, hemp, tapes. (Up to 1 inch)

■ green
viscous liquid
T°: -60 à +150°C
Shearing strength:
> 15 N/mm²
M10 steel > 25N.m
Setting time at
20°C: 10 à 25 min

PMUC 16-071

6328F3	50 ml bottle	x6
--------	--------------	----



ORAJOINT

324

FLAT SEALING AND THREADED

Sealing of machined close mating surfaces. Withstands vibrations, industrial fluids, oils and gases. Recommended for complicated close mating surfaces: pump housings, motors, gearboxes etc. Also recommended for threaded metal seals with «medium resistance» when dismantling.

■ red
Handling time:
5 to 25 mn
T°: -60 to +180°C
Shearing strength:
> 15 N/mm²



PMUC 16-075

6324T2	50 ml tube	x6
--------	------------	----

PORAJOINT

333

FLAT AND THREADED SEAL

Sealing gel with high adhesive power for all flanges, including vertical flanges. Replaces conventional seals with complex shapes: pump housings, motors, gear boxes etc. Also recommended for threaded metal seals with «medium resistance» when dismantling.

■ red
T°: -60 to +150°C
Shearing strength:
> 8 N/mm²
Setting time at 20°C:
10 to 25 mn

PMUC 16-072

6333T2	50 g tube	x6
--------	-----------	----



NUCSEAL N

346

NON HARDENING, HALOGEN-FREE

For sealing close mating surfaces and threaded fittings subject to severe vibrations. Replaces or bonds paper gaskets and other pre-cut gaskets. Helps create leak-proof seals of any shape, including complex ones. Instantly forms a low pressure seal.

■ blue
viscous liquid
T°: -50 to +300°C
Cl - F - S - Br:
< 200 ppm

PMUC 17-0386

6346T3	100 g tube	x12
--------	------------	-----

LUBRISEAL RTV

100

TRANSPARENT ADHESIVE MASTIC

Flexible bonding and sealing. Metal, glass and ceramic parts, expansion joints, wire insulation, etc. Soundproofing, insulation and mechanical applications.

transparent
T° : -65 à +250°C
Film formation:
10mn
Complete drying :
24h
Shore A hardness:
25 - 33

PMUC 17-108

6100T3	Tube 100 g	x12
6100C3	Cartridge 310 ml	x12



FASTENING RING

BLOCK BAGUE

314

FIXATION FORTE - JEU < 0,05 MM

Fluid resin recommended for small gaps. Fastening of rings, pulleys, bearings etc. with high shearing strength.

■ green
Handling time:
on steel 10 to 25mn
T°: -60 to +150°C
Shearing strength:
> 20 N/mm²

PMUC 16-051



6314F6	50 ml bottle	x6
--------	--------------	----

BLOCK ROULEMENT

318

MEDIUM RESISTANCE - GAP < 0.05MM

Affixing parts which need to be dismantled with standard tools in case of wear. Fittings reinforcement. Increase assemblies reliability.

■ red
Handling time:
on steel 10 to 25 mn
T°: -60 to +150°C
Shearing strength:
> 15 N/mm² (24 hrs)

PMUC 16-051



6318F3	Bottle 50 ml	x6
--------	--------------	----

WIRE BRAKES

FREIN FAIBLE

307

MODERATE RESISTANCE, LOW VISCOSITY

For all assemblies to be dismantled easily using standard tools and with small gaps, on thin threads and small screws.

PMUC 19-074

■ blue liquid
T°: -60 to +150°C
Setting time/ steel:
10 to 25 mn
CD 24 hrs/
M10 steel: 7 to 13 N.m



6307F3 50 ml bottle x6

FREIN MOYEN

304

MEDIUM RESISTANCE, FLUID THREAD LOCK

For all assemblies to be dismantled easily using standard tools. Fluidity perfect for thin threads and small fastenings.

PMUC 19-049

■ red liquid
T°: -60 to +150°C
Setting time/ steel:
10 to 25 mn
CD 24 hrs/
M10 steel:
15 - 20 N.m



6304F3 50 ml bottle x6

FREINAGE FORT

300

STRONG RESISTANCE

Permanent fixing of threads and dowels that are not to be dismantled. Fluidity perfect for thin threads and small fastenings.

PMUC 19-048

■ green liquid
T°: -60 to 150°C
Setting time/ steel:
10 to 25 mn
CD 24 hrs/
M10 steel:
> 25 N.m



6300F3 50 ml bottle x6



PROTECT

ANTIPERL ECO

808

WATER-BASED ANTI-WELD SPATTER

Silicone-free and solvent-free anti-welding spatter product. Non-toxic. Water emulsion of non-stick agents, to be used for the protection of assemblies and tools in welding operations. Removed with water.

PMUC 22-0082

■ milky white
Viscosity:
1 to 3 cPs
Flash point:
Non-VOC
content: 0%



6808A4 650 ml aerosol x12
6808J1 5 l jerrycan x4

MV ROUGE

010

IDENTIFICATION - MARKING - CODING

Marking and identification varnish for validating the warranty. This varnish is used to provide assembly and installation security. Opening the device breaks the seal and provides a quick, visual indication that the device has been tampered with. Can be applied to screws, clips, fastenings and miscellaneous components. Renders screws, bolts and rivets tamper-proof.

■ red
T°: -40 to +200°C
Dust free: 1 min



1010FB 90 ml bottle x6

ADHERENT COURROIES 953

STOPS DRIVE BELTS FROM SLIPPING

Triples belt adherence for rubber, leather, canvas, or composite. Prevents belts from hardening while eliminating power loss. Treated belts wear more slowly and transmit power more effectively. Helps position pre-cut gaskets onto crankcases. For treating conveyor belts to provide better grip.

■ yellow liquid
T° Max : +80°C



4953A4 650 ml Aerosol x12

NZA B

706

GLOSS GALVANISATION

Exceptional, long-lasting protection against corrosion (up to 3 years) for all metal parts. Coating with high zinc content giving a gloss finish. Can be used as a finish under-layer. Efficient, even in corrosive and marine conditions.

■ Shiny grey
T°: -50 to +200°C
Salt spray:
> 400 h for 20 µm
Spray coating:
5 µm
Volume coverage:
2 m² / aerosol



4706A4 650 ml aerosol x12
2706S1 5 kg tub x2



ORAPI

CLEAN & PROTECT TOGETHER

France/Global headquarters

Parc Industriel de la Plaine de l'Ain
225, allée des Cèdres
01150 Saint-Vulbas
Tel.: +33 (0)4 74 40 20 20
Fax: +33 (0)4 74 40 20 21
Web: www.orapi.com
E-mail: contact@orapi.com

EXPORT DEPARTMENT

Tel.: +33 (0)4 74 40 20 25
Fax: +33 (0)4 74 40 20 26
E-mail: export@orapi.com

NORTHERN EUROPE

BELGIUM

ORAPI APPLIED BELGIUM S.A.
Kapelsesteenweg 292
2930 Brasschaat
Tel.: +32 2 2800 736
E-mail: sales@orapiapplied.be

NORWAY

ORAPI APPLIED NORWAY
Pb 1573 - 4688 Kristiansand
Tel.: +47 333 66 000
Fax: +47 333 66 008
E-mail: kundeservice@orapi.no

UNITED KINGDOM

ORAPI APPLIED Ltd
Spring Road, Smethwick
West Midlands, B66 1PT
Tel.: +44 121 525 4000
Fax: +44 121 525 4919
E-mail: info@orapiapplied.com

FINLAND

ORAPI NORDIC OY AB
Salpakuja 6 - 01200 Vantaa
Tel.: +358 9 894 6430
Fax: +358 9 8946 4322
Web: www.orapinordic.net
E-mail: sales@orapinordic.net

NETHERLANDS

ORAPI APPLIED
NEDERLAND B.V.
A Van Leeuwenhoekweg
2408AN Alphen Aan Den Rijn
Tel.: +31 172 43 72 21
Fax: +31 172 43 69 01
Web: www.orapiapplied.com
E-mail: sales@orapiapplied.com

POLAND

ORAPI TRANSNET Sp. z o.o.
ul. Sremska 75a - 62-050 Mosina
Tel.: +48 61 813 86 40
Fax: +48 61 813 86 91
E-mail: mariusz.polkowski@orapi-transnet.pl

SWEDEN

ORAPI NORDIC OY AB
Vaksala Eke Hus C
75594 Uppsala
Tel.: +46 18 506 010
Fax: +46 18 500 910
Web: www.orapi.SE
E-mail: info@orapi.se

SOUTHERN EUROPE

ITALY

ORAPI ITALIA SRL
Via Nettunense Km 25,00
04011 Aprilia (Lt)
Tel.: +39 06 916 10576
Fax: +39 06 918 02468
E-mail: info@orapi.it

SPAIN

ORAPI TRANSNET
ESPAÑA S.L.
Pol. Ind. Castro Romano, Nave 20
22600 Sabiñánigo (Huesca)
Tel./Fax: +34 974 480 828
E-mail: adminote@orapi.com

AMERICA

CANADA

ORAPI CANADA LTD
7521 Henri Bourassa Est
Montréal - Québec H1E1N9
Tel.: +1 514 735 32 72
Fax: +1 514 735 85 50
E-mail: jean.fallouey@orapi-canada.com

MARTINIQUE

Martinique hygiène
Emballage Sarl
9 Rue des Amarreuses
Zac La Marie
97224 Ducos
Tel.: 0596 77 2097
E-mail: info@mhe-martinique.com

ASIA & MIDDLE EAST

SINGAPORE

ORAPI APPLIED (S) Pte Ltd
No.26 Tuas Avenue 13
Singapore 638992
Tel: +65 6265 2888
Fax: +65 6268 6474
Email: sin.sales@orapiasia.com

THAILAND

ORAPI APPLIED (T) CO. Ltd
55/75 Khlong Lamchiak Road,
Nuanchan, Buengkum
Bangkok 10230, Thailand
Tel: +66 2508 1342
Fax: +66 2508 1343
Email: thai.sales1@orapiasia.com

MALAYSIA

ORAPI APPLIED (M) Sdn Bhd
No.10, Jalan PJU 3/49 - PJU 3,
Sunway Damansara 47810 Petaling
Jaya - Selangor, Malaysia
Tel: +60 3 7805 3805
Fax: +60 3 7880 5805
Email: msia.sales@orapiasia.com

UNITED ARAB EMIRATES

ORAPI MIDDLE EAST L.L.C.
729 Business Village, Main Building
Block B - PO Box 120509 - Dubai, UAE
Tel: +971 (0) 4294 2947
Fax: +971 (0) 4294 2948
Email: uae.sales@orapi.ae

PACIFIC

AUSTRALIA

VICTORIA LUB Pty Ltd
Factory 24, 29-39 Kirkhan Road West
Keysborough, Po Box 816
Victoria 3174
Tel.: +613 9701 5373
Fax: +613 9701 5532
E-mail: info@viclube.com.au

NEW CALEDONIA

SFAC Sarl
27, rue Ampère - ZI Ducos - BP 3725
98846 Nouméa Cedex
Tel: +687 77 72 19
Fax: +687 27 20 67
Email: sfac@sfac.nc

AFRICA

MAURITIUS

PROLUB Cie Ltd
62 Pailles Road - Port Louis
Tel.: +230 286 6328
Fax: +230 286 6330
E-mail: admin.prolub@intnet.mu

SOUTH AFRICA

ORAPI AFRICA Ltd
Unit 2 HGI Bridgeway Business Park
434 Sam Green & Pinnacle Road
Rietfontein 63, 1401
P.O. Box 0123, Glen Erasmia, 1638
Tel.: 082 416 98 32
E-mail: hilgard@orapiafrica.co.za

ORAPI designs, manufactures and markets all the consumable products needed for the maintenance, industrial maintenance and construction of machines.

To meet all your needs,
discover our high-tech, reliable and tested products
to ensure a perfect manufacturing or maintenance of your machines.



ORAPI
CLEAN & PROTECT TOGETHER

Parc Industriel de la Plaine de l'Ain
225, allée des Cèdres
01150 Saint-Vulbas - FRANCE

Tel. : + 33 (0)4 74 40 20 25 - Fax : + 33 (0)4 74 40 20 21
contact@orapi.com

www.orapi.com